

Specification

Nominal Voltage	12V	
Watts(15min Rate)	33.3 Watts at 1.67V/cell	
Dimension	Length	151±2mm (5.95 inches)
	Width	65±1mm (2.56 inches)
	Container Height	93.5±1mm (3.68 inches)
	Total Height (with Terminal)	99±1mm (3.90 inches)
Approx Weight	Approx 2.66 kg (5.87lbs)	
Terminal	T1 / T2	
Container Material	ABS	
Rated Capacity	8.60 AH/0.43A	(20hr, 1.80V/cell, 25°C/77°F)
	7.98 AH/0.798A	(10hr, 1.80V/cell, 25°C/77°F)
	7.10AH/1.42A	(5hr, 1.75V/cell, 25°C/77°F)
	6.45 AH/2.15A	(3hr, 1.75V/cell, 25°C/77°F)
	5.96 AH/5.96A	(1hr, 1.60V/cell, 25°C/77°F)
Max. Discharge Current	135A (5s)	
Internal Resistance	Approx 17mΩ	
Operating Temp. Range	Discharge	-15~50°C (5~122°F)
	Charge	0~40°C (32~104°F)
	Storage	-15~40°C (5~104°F)
Nominal Operating Temp. Range	25±3°C (77±5°F)	
Cycle Use	Initial Charging Current less than 2.7A. Voltage	
	14.4V~15.0V at 25°C(77°F)Temp. Coefficient -30mV/°C	
Standby Use	No limit on Initial Charging Current Voltage	
	13.5V~13.8V at 25°C(77°F)Temp. Coefficient -20mV/°C	
Capacity affected by Temperature	40°C (104°F)	103%
	25°C (77°F)	100%
	0°C (32°F)	86%
Self Discharge	Leoch LPX series batteries may be stored for up to 6 months at 25°C(77°F) and then a freshening charge is required. For higher temperatures the time interval will be shorter.	



Applications

- ◆ UPS (High rate)
- ◆ High power backup supply
- ◆ Emergency power supply
- ◆ Starting system
- ◆ Power tools
- ◆ Emergency lighting
- ◆ Electric starting



Constant Current Discharge (Amperes) at 25 °C (77°F)

F.V/Time	5min	10min	15min	20min	30min	45min	1h	2h	3h	4h	5h	6h	8h	10h	20h
1.85V/cell	28.6	19.1	15.0	12.4	9.24	6.71	5.24	2.84	2.03	1.61	1.34	1.16	0.927	0.776	0.421
1.80V/cell	32.1	20.9	16.2	13.2	9.65	6.95	5.43	2.93	2.09	1.64	1.38	1.19	0.956	0.798	0.430
1.75V/cell	35.3	22.1	17.2	13.9	10.0	7.20	5.61	3.03	2.15	1.70	1.42	1.23	0.994	0.819	0.439
1.70V/cell	37.6	23.3	18.0	14.3	10.4	7.42	5.75	3.12	2.22	1.75	1.46	1.26	1.00	0.834	0.444
1.67V/cell	39.3	24.1	18.5	14.8	10.7	7.60	5.86	3.17	2.26	1.79	1.49	1.28	1.02	0.843	0.447
1.60V/cell	40.5	25.0	18.9	15.1	10.9	7.72	5.96	3.22	2.28	1.81	1.51	1.30	1.03	0.850	0.450




Constant Power Discharge (Watts/cell) at 25 °C (77°F)

F.V/Time	5min	10min	15min	20min	30min	45min	1h	2h	3h	4h	5h	6h	8h	10h	20h
1.85V/cell	52.8	35.6	28.2	23.5	17.6	12.9	10.1	5.50	3.95	3.14	2.63	2.28	1.83	1.54	0.836
1.80V/cell	58.4	38.4	30.1	24.7	18.2	13.2	10.4	5.66	4.06	3.20	2.69	2.34	1.88	1.58	0.851
1.75V/cell	63.4	40.1	31.6	25.7	18.8	13.6	10.7	5.82	4.15	3.30	2.78	2.41	1.95	1.61	0.867
1.70V/cell	66.5	41.8	32.6	26.3	19.4	14.0	10.9	5.97	4.27	3.39	2.84	2.46	1.97	1.64	0.877
1.67V/cell	68.4	42.6	33.3	27.0	19.8	14.2	11.1	6.05	4.33	3.45	2.89	2.49	2.00	1.65	0.881
1.60V/cell	69.5	43.6	33.6	27.2	20.0	14.3	11.2	6.12	4.37	3.47	2.92	2.52	2.01	1.67	0.885


Dimensions

T1 Terminal


Unit: mm [inches]




Discharge Characteristics





Float Charging Characteristics



Temperature Effects in Relation to Battery Capacity



Effect of Temperature on Long Term Float Life



Self Discharge Characteristics

- A** No supplementary charge required
(Carry out supplementary charge before use if 100% capacity is required.)
- B** Supplementary charge required before use. Optional charging way as below:
 1. Charged for above 3 days at limited current 0.25CA and constant volatge 2.25V/cell.
 2. Charged for above 20hours at limited current 0.25CA and constant volatge 2.45V/cell.
 3. Charged for 8-10hours at limited current 0.05CA .
- C** Supplementary charge may often fail to recover the capacity.
The battery should never be left standing till this is reached.

Sales Office

China sales office:

Add: 5th Floor, Xinbaohui Bldg., Nanhai Blvd.,
Nanshan, Shenzhen, China. 518052
Tel: +86-755-86036060 (100 lines)
Fax: +86-755-26067269
E-mail: export@leoch.com
Http://www.leoch.com

HongKong sales office:

Workshop C, 33/F, TML Tower,
No. 3 Hoi Shing Road, Tsuen Wan,
New Territories, Hong Kong
Tel: +852 35786666
Fax: +852 21170016
E-mail: sales.hk@leoch.com

Singapore sales office:

Add: No. 1 Tech Park Crescent,
Singapore 638131
Tel: +65 68636078
Fax: +65 68636079
Email sales.sg@leoch.com
Http://www.leoch.com

North America sales office:

Add: 19751 Descartes, Unit A,
Foothill Ranch, CA 92610, USA
Tel: 949-588-5853
Fax: 949-588-5966
E-mail: sales@leoch.us
Http://www.leoch.us

Europe sales office:

Add: 9B Wheatstone Court. Waterwells
Business Park, Gloucester, GL2-2AQ,
UK United Kingdom
Tel: +44(0) 1452 729428 / 1452 729696
Fax: +44 (0)1452-690125
E-mail: Sales.Europe@leoch.com